

CONCRETE CYLINDER GRINDING MACHINE

This polishing machine for concrete cylinder mold measures the compressive strength with uniform surface contacts without eccentricity by polishing the surface of concrete cylinder mold (100, 150 mm) etc, with diamond. This prevents the inconvenience of capping with compound or cement glue, etc.



Technical Specifications :

Model Number	NL 4034 X / 003
Alternate Code	HJ-3751
Unit	3 Unit (Ø100mm) or 1 Unit (Ø150mm)
Polishing Motor	1800 r.p.m
Speed Control (Polishing)	Volume Control (App. 0.2 ~ 2.5 mm/min)
Timer (Polishing)	Electric Timer
Water Supply	Automatic Water Supply
Polishing Wheel	Diamond Wheel 8 inch
Dimension(LxWxH)	600 x 850 x 1350mm
Weight	290kg
Power	380~415V, 750kW, 3Ph, 50/60 Hz

*1 Copy of Manual Instruction

Unit Consists Of :

Model Number	Parts Description	Qty
NL 4034 X / 003 - P 001	4" or 100mm Dia. Specimen Holder Base	1pc
NL 4034 X / 003 - P 002	4" or 100mm Dia. Specimen Guide Plate	1pc
NL 4034 X / 003 - P 003	6" or 150mm Dia. Specimen Guide Plate	1pc
NL 4034 X / 003 - P 004	Tubing Set (Drain Tube x 2.5m), (Cooling Water Supplied Tube x 3m)	1set

Optional Accessories :

Model Number	Parts Description
NL 4034 X / 003 - A 001	8" Dia. Grinding Disc